



SECTION 1-1

FOOTING MINIMUM WIDTH (mm) FOR VARIOUS DEPTH

POST SPACING (m)	250	300	350	400
1	1450	1345	1250	1170
1.5	1200	1100	1020	955
2	1040	950	885	830
2.5	930	850	790	740
3	850	775	720	675
3.5	785	720	670	625
4	735	675	625	585

FOOTING MINIMUM DEPTH (mm) FOR VARIOUS WIDTHS

POST SPACING (m)	700	800	900	1000
1	600	600	600	555
1.5	600	580	455	365
2	570	430	335	270
2.5	450	340	270	250
3	375	285	250	250
3.5	320	250	250	250
4	275	250	250	250

- NOTES:
1. ALL DIMENSIONS IN MILLIMETRES.
 2. MINIMUM STRENGTH OF CONCRETE FOOTING - 20MPa.

REVISIONS		REFERENCES		DRAWING NUMBER		REFERENCE DRAWINGS		SCALE		NAME		DATE		DRAWING No.	
REV	DATE	DESCRIPTION	DRAWN	CHECKED	APPROVED			SCALE	SIZE						
0	20/06/11	ISSUED FOR INFORMATION	AUSTEC	TC	TC			APPROVED	A1						WR-STD-83
															REV. 0

INGAL CIVIL PRODUCTS
 5145 ANOS ROAD
 AUSTRALIA 3566
 PH. +61 2 9827 3333
 FAX. +61 2 9827 3300
 www.ingalcivil.com.au

PROJECT
 FLEXFENCE
 WIRE ROPE SAFETY BARRIER

INGAL CIVIL PRODUCTS
 REFERENCE No.